




R12-110-230V



R12-100-/200-/110-/020-



1- and 2-pole, 16A/250V AC

Modular devices for DIN 60715 TH35 rail mounting with manual control and switch position indicator. 1 module = 18mm wide, 55mm deep.

100% time on. Control power demand 1.9W.

Contacts: 1 NO, 2 NO, 1 NO + 1 NC, 2 NC (closed-circuit current relay, 230V only).

Contact gap 3mm.

Contact/contact test voltage 2000V and control connections/contact test voltage 4000V.

25A devices XR12, page 19-4. Retrofittable auxiliary contact KM12, page 18-3.

The pin-compatible ER12DX-UC, ER12-200-UC and ER12-110-UC electronic switching relays can also be used.

The universal control voltage UC covers the voltage ranges of 8 to 253V AC at 50-60Hz and 10 to 230V DC.

R12-100-12V	1 NO 16A	EAN 4010312200421	23,20 €/pc.
R12-100-230V	1 NO 16A	EAN 4010312200445	23,20 €/pc.
R12-100-8V, 24V, 12V DC, 24V DC	1 NO 16A		25,10 €/pc.
R12-200-12V	2 NO 16A	EAN 4010312200506	29,20 €/pc.
R12-200-230V	2 NO 16A	EAN 4010312200520	29,20 €/pc.
R12-200-8V, 24V, 12V DC, 24V DC	2 NO 16A		31,20 €/pc.
R12-110-12V	1 NO + 1 NC 16A	EAN 4010312200469	29,20 €/pc.
R12-110-230V	1 NO + 1 NC 16A	EAN 4010312200483	29,20 €/pc.
R12-110-8V, 24V, 12V DC, 24V DC	1 NO + 1 NC 16A		31,20 €/pc.
R12-020-230V	2 NC 16A	EAN 4010312201572	29,10 €/pc.