

Tap-radio® temperature controller TF-TRHB55

Eltako



TF-TRHB55 Tap-radio® temperature controller

Wireless temperature controller with hand wheel pure white glossy for single mounting 80x80x27mm or mounting in the 55 mm switch system. With battery (lifetime 4 years). Smart Home sensor.

The temperature controller can be taught-in into the relay actuator TF61R or the heating cooling actuator FHK and into the GFVS software. At a setpoint or current temperature change from min. 0,15°C, the temperature controller sends a wireless telegram within 60 seconds.

If there is no change, a status message is sent every 5 minutes. A jumper defines the function mode. In the TF61 operating mode, only ON or OFF are sent, depending on the difference between setpoint and actual temperature. Measurement accuracy is approx. 1°C.

The **setpoint temperature** is set with the hand wheel from 12°C to 28°C.

In the ❄️ position, the set temperature is 8°C (frost protection).

We recommend stainless-steel countersunk 2.9x25 mm, DIN 7982 C, for screw connections.

Both with rawl plugs 5x25 mm and with 55 mm switch boxes. Set of 2 stainless-steel countersunk screws 2,9x25 mm and plugs 5x25 mm are enclosed.



private series

TF-TRHB55

Temperature controller with hand wheel,
pure white glossy

EAN 4010312318317

66,80 €/pc.