



TCPRS1+

TCPRS1+, RS-485 / Ethernet converter / Wi-Fi

Code: M62422.

> Protocol: TCP/IP | UDP | Modbus TCP/IP | HTTP (Web server)

> Communications: Ethernet, Wi-Fi

Description

The **TCPRS1+** is a gateway designed to convert a physical environment (RS-485) to Ethernet and/or Wi-Fi. The device features a Web Server and the "**MyConfig Wifi**" app (Android), from which the user can fully edit the configuration parameters of the device.

Other features:

- The device is for installation inside a medium or low voltage electric panel or enclosure, with DIN rail mounting (IEC 60715).
- The TCPRS1+ comes with DHCP enabled by default.
- Connect up to 32 devices on the RS-485 communications bus.

Application

For any installation that has multiple RS-485 communications devices that require monitoring via Wi-Fi or Ethernet.



TCPRS1+

RS-485 to Ethernet converter / Wi-Fi

Code: M62422.

Specifications

AC power supply

Installation category	CAT III
Consumption	2 ... 7 VA
Frequency	50 ... 60 Hz
Nominal voltage	100 ... 264 V ~

DC power supply

Installation category	CAT III
Consumption	1,6 ... 2 W
Nominal voltage	120 ... 300 Vdc

Mechanical characteristics

Size (mm) width x height x depth	35 x 109.45 x 70 (mm)
Screw type	Flat, M2.5
Envelope	Self-extinguishing V0 plastic
Torque setting	≤ 0,4 Nm
Communications cable cross-section	2.5 mm ²
Cable gauge at power supply terminals	2.5 mm ²
Fastening	DIN rail
Weight (kg)	0,126

Environmental characteristics

Protection class	IP30, Front: IP40 IK08
Relative humidity (without condensation)	5 ... 95%
Storage temperature	-20 ... +70 °C
Operating temperature	-20 ... +60 °C

Communications

Protocol	TCP/IP UDP Modbus TCP/IP HTTP (Web server)-REST
Type	RS-485/Ethernet/Wi-Fi

Standards

Electrical safety, Maximum height (m)	2000
Standards	EN 62368-1:2020/A11:2020/ AC:2020-05, EN 50663: 2017, ETSI EN 301 489-1 V2.2.3, ETSI EN 301 489-17 V3.2.4, ETSI EN 301 893 V2.1.1

User interface

LED	6 LED
-----	-------



TCPRS1+

RS-485 to Ethernet converter / Wi-Fi

Code: M62422.

TCPRS1+

RS-485 / Ethernet / Wi-Fi converter

CODE	TYPE	Communications	Protocol
M62422.	TCPRS1+	RS-485, Ethernet, Wi-Fi	TCP/IP UDP Modbus TCP/IP HTTP (Web server)



TCPRS1+

RS-485 to Ethernet converter / Wi-Fi

Code: M62422.

Dimensions

