




- Suitable for diodes and resistors
- Small size



PRESENTATION PURPOSE ONLY



PRESENTATION PURPOSE ONLY



CODE	XCCM08SV	XCCM16SV	XCCM24SV
TYPE	CCM08SV	CCM16SV	CCM24SV
GENERAL TECHNICAL DATA			
Number of poles	8	16	24
Version	single feed-through	single feed-through	single feed-through
Input rated voltage	0...100 V ±10%	0...100 V ±10%	0...100 V ±10%
Input rated current	4 A max. (on common)	4 A max. (on common)	4 A max. (on common)
Operating temperature	-20...+60°C	-20...+60°C	-20...+60°C
Standards approvals	—	—	—
Overvoltage category /pollution degree	II / 2	II / 2	II / 2
Protection degree	IP 00	IP 00	IP 00
Connection terminal	2.5 mm ² screw	2.5 mm ² screw	2.5 mm ² screw
Status indication	—	—	—
Dimensions	25x66x93 mm	47x66x93 mm	70x66x93 mm
Approximate weight	—	—	—
Housing material	UL94V-0 plastic material	UL94V-0 plastic material	UL94V-0 plastic material
Mounting informations	vertical on rails, side by side	vertical on rails, side by side	vertical on rails, side by side
APPROVALS	CE	CE	CE
ACCESSORIES			
Mounting rail IEC60715 TH35 75	PR003, PR903, PR005, PR939	PR003, PR903, PR005, PR940	PR003, PR903, PR005, PR941
Mounting rail IEC60715 TH35 15	PR007, PR907, PR006, PR940	PR007, PR907, PR006, PR941	PR007, PR907, PR006, PR942
Marking tag	—	—	—