




NOTE
The module is equipped with 1N4007 diodes



PRESENTATION PURPOSE ONLY



PRESENTATION PURPOSE ONLY



CODE	CDM08AC	XCDM08AC	CDM16AC	XCDM16AC	CDM24AC	XCDM24AC
TYPE	CDM08AC		CDM16AC		CDM24AC	
GENERAL TECHNICAL DATA						
Number of poles	8		16		24	
Version	common anode		common anode		common anode	
Input rated voltage	0...220 V ±10%		0...220 V ±10%		0...220 V ±10%	
Input rated current	1 A channel / 15 A on common		1 A channel / 15 A on common		1 A channel / 15 A on common	
Operating temperature	-20...+60°C		-20...+60°C		-20...+60°C	
Standards approvals	—		—		—	
Overvoltage category /pollution degree	II / 2		II / 2		II / 2	
Protection degree	IP 00		IP 00		IP 00	
Connection terminal	2.5 mm ² screw		2.5 mm ² screw		2.5 mm ² screw	
Status indication	—		—		—	
Dimensions	45x65x93 mm		92x65x93 mm		137x65x93 mm	
Approximate weight	—		—		—	
Housing material	UL94V-0 plastic material		UL94V-0 plastic material		UL94V-0 plastic material	
Mounting informations	vertical on rails, side by side		vertical on rails, side by side		vertical on rails, side by side	
APPROVALS	CE		CE		CE	
ACCESSORIES						
Mounting rail IEC60715 TH35 75	PR003, PR903, PR005, PR945		PR003, PR903, PR005, PR946		PR003, PR903, PR005, PR947	
Mounting rail IEC60715 TH35 15	PR007, PR907, PR006, PR946		PR007, PR907, PR006, PR947		PR007, PR907, PR006, PR948	
Marking tag	—		—		—	